

CLAIM AMENDMENTS

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Canceled)
7. (Canceled)
8. (Canceled)
9. (Canceled)
10. (Canceled)
11. (Canceled)
12. (Canceled)
13. (Canceled)
14. (Canceled)
15. (Canceled)
16. (Canceled)
17. (Canceled)
18. (Canceled)
19. (Canceled)
20. (Canceled)
21. (Canceled)
22. (Canceled)
23. (Canceled)
24. (Canceled)
25. (Canceled)
26. (Canceled)
27. (Canceled)
28. (Canceled)
29. (Canceled)

30. (Canceled)
31. (Canceled)
32. (Canceled)
33. (Canceled)
34. (Canceled)
35. (Canceled)
36. (Original) The vehicle light source in claim 57,
wherein the lamp capsule is replaceable , and
wherein the support includes a base structure having a thermally conductive connection to
a heat sink.
37. (Original) The vehicle light source in claim 36, wherein the connection is to an attached
spacially extended heat radiator forming a portion of the lamp capsule.
38. (Original) The vehicle light source in claim 37, wherein the heat radiator is a flange.
39. (Canceled)
40. (Original) The vehicle light source in claim 37, wherein the connection is a thermally
conductive coupling to a thermally conductive portion of a vehicle.
41. (Canceled)
42. (Canceled)
43. (Original) The vehicle light source in claim 36, wherein the LEDs are mounted in a
plurality of bands extending around the support.

44. (Original) The vehicle light source in claim 36, wherein the LEDs are arranged in a plurality of separate circuits coupled to separate inputs enabling alternative light outputs.
45. (Original) A vehicle light assembly comprising:
- a) a replaceable lamp capsule having a support defining a lamp axis extending in a forward direction towards a field to be illuminated, one or more LEDs mounted on the support, each LED having a predominate LED axis of light emission, the majority of the LEDs being oriented so the respective LED axes form an angle with respect to the forward lamp axis direction of ninety or more degrees;
 - b) a reflector having reflective surface formed with a rear opening to receive the LEDs of the lamp capsule therethrough, the reflector further having a height measured along an axis of the reflector and a maximal diameter measured transverse to the axis, wherein the reflector is offset from and oriented with respect to a majority of the LEDs to intercept the LED axes, and reflect light emitted from the LEDs generally in the forward direction to the field to be illuminated,
 - c) wherein the ratio of the reflector diameter to the reflector height is more than 1.0, and
 - d) wherein the reflector height is less than 5.0 centimeters.
46. (Original) The vehicle light assembly in claim 45, further including a lens enclosing the lamp capsule in the reflector, wherein the reflector and lens assembly has an interior axial measurement from an inner face of the lens to an transverse plane intersecting the reflector at the formed opening of less than 4.0 centimeters.
47. (Original) A vehicle light assembly of claim 45, further including a coupling to mount the vehicle light assembly in an indentation formed in a vehicle hull.
48. (Original) The vehicle light source in claim 36, wherein the support is substantially cylindrical.

49. (Original) A vehicle light source comprising:
a replaceable lamp capsule having a support, a plurality of LEDs mounted on the support,
wherein the support is made from material having a high thermal conductivity to conduct
heat away from the plurality of LEDs,
wherein the support includes a base structure having a thermally conductive connection to
a heat sink
wherein the support is substantially cylindrical, and
wherein the base structure includes a heat conductive flange and a coupling to press the
flange to a thermally conductive portion of a vehicle hull.
50. (Original) A vehicle light source comprising:
a replaceable lamp capsule having a support, a plurality of LEDs mounted on the support,
wherein the support is made from material having a high thermal conductivity to conduct
heat away from the plurality of LEDs,
wherein the support includes a base structure having a thermally conductive connection to
a heat sink, and
wherein the LEDs are supported on an intermediate flexible substrate, and the flexible
substrate is bent to conform with the exterior contour of the support, the flexible substrate
being mechanically coupled to the support.
51. (Original) The vehicle light source in claim 50, wherein for flexible substrate is
thermally coupled to the support for heat conduction from LEDs through the flexible
substrate to the support.
52. (Original) The vehicle light source in claim 50, wherein the flexible substrate is
supported in a groove formed on the support.
53. (Original) The vehicle light source in claim 50, wherein the LEDs are supported
respectively on spoke portions of a flexible hub and spokes structure.

54. (Original) The vehicle light source in claim 53, wherein the hub and spoke structure provides an electrical connection in the hub portion.
55. (Original) A vehicle light source comprising:
a replaceable lamp capsule having a support, a plurality of LEDs mounted on the support, wherein the support is made from material having a high thermal conductivity to conduct heat away from the plurality of LEDs,
wherein the support includes a base structure having a thermally conductive connection to a heat sink, and
wherein the support includes an umbrella like head portion, and the LEDs are mounted with the head portion positioned substantially intermediate the LEDs and the field to be illuminated.
56. (Original) The vehicle light source in claim 53, wherein the support includes a lower sidewall including a reflective skirt directing light from the LEDs away from the support.
57. (Original) A vehicle light source comprising:
a lamp capsule having a support, wherein the support includes an umbrella like head portion,
a plurality of LEDs mounted on the support, and positioned with respect to the head portion so that the head portion is substantially intermediate the LEDs and the field to be illuminated, wherein the support is made from material having a high thermal conductivity to conduct heat away from the plurality of LEDs.
58. (Original) A vehicle light assembly comprising:
a lamp capsule having a support, wherein the support includes an umbrella like head portion,
a plurality of LEDs mounted on the support, and positioned with respect to the head portion so that the head portion is substantially intermediate the LEDs and the field to be illuminated, thereby substantially blocking direct view of the LEDs, wherein the support

is made from material having a high thermal conductivity to conduct heat away from the plurality of LEDs, wherein the support defines a lamp axis extending in a forward direction towards a field to be illuminated, and the plurality of LEDs mounted on the support each LED have a predominate LED axis of light emission, the majority of the LEDs being oriented so the respective LED axes form an angle with respect to the forward lamp axis direction of ninety or more degrees; and

a reflector having reflective surface formed with a rear opening to receive the LEDs of the lamp capsule there through, the reflector further having a height measured along an axis of the reflector and a maximal diameter measured transverse to the axis, wherein the reflector is offset from and oriented with respect to a majority of the LEDs to intercept the LED axes, and reflect light emitted from the LEDs generally in the forward direction to the field to be illuminated.

- 59. (Original) The vehicle light assembly in claim 58, wherein the support includes a lower sidewall including a reflective skirt directing light from the LEDs away from the support.
- 60. (Cancelled)
- 61. (Cancelled)
- 62. (Cancelled)
- 63. (Cancelled)
- 64. (Cancelled)
- 65. (Cancelled) A light source for use with a concave reflector to direct light to a field to be illuminate , the light source comprising:
a support including an umbrella like head portion;

one or more LEDs mounted on the head portion, and positioned with respect to the head portion so that the head portion is substantially intermediate the one or more LEDs and the field to be illuminated;

the support further including a post having a first end supporting the head portion and a second end axially extended away from the first end, the second end being mechanically fixed relative to the reflector to position the head portion away from the reflector; and

wherein the one or more LEDs are arranged on the head portion to face the reflector and direct light emitted from the one or more LED towards the reflector for reflection to the field to be illuminated.

CLAIM STATUS:

Claims 1 - 35: (Canceled)

Claims 36 - 38: (Original)

Claim 39: (Canceled)

Claim 40: (Original)

Claims 41 - 42: (Canceled)

Claims 43 - 59: (Original)

Claims 60 - 65: (Canceled)